



	CARRIAGE HOUSE												TRADITIONAL									
	AMARR CARRIAGE COURT CC4000	AMARR CLASSICA CL1000	AMARR CLASSICA CL2000	AMARR CLASSICA CL3000	AMARR OAK SUMMIT OS1000	AMARR OAK SUMMIT OS2000	AMARR OAK SUMMIT OS3000	AMARR DESIGNER'S CHOICE DC3200	AMARR HILLCREST HI1000	AMARR HILLCREST HI2000	AMARR HILLCREST HI3000	AMARR HERITAGE HR1000	AMARR HERITAGE HR2000	AMARR HERITAGE HR3000	AMARR STRATFORD ST1000	AMARR STRATFORD ST2000	AMARR STRATFORD ST3000	AMARR OLYMPUS OL3200	AMARR LINCOLN LI1000	AMARR LINCOLN LI2000	AMARR LINCOLN LI3000	
PANEL DESIGNS (Safe Guard)		✓	✓	✓	✓	✓	✓					✓	✓	✓	✓	✓						
Short												•	•	•	•	•	•	•	•	•	•	•
Long												•	•	•	•	•	•	•	•	•	•	•
Flush													•				•					•
Ribbed													•				•					•
Carriage House	18 Designs	7 Designs	7 Designs	7 Designs	4 Designs	4 Designs	4 Designs	4 Designs	4 Designs	4 Designs	4 Designs											
CONSTRUCTION LAYERS	4	1	2	3	1	2	3	3	1	2	3	1	2	3	1	2	3	3	1	2	3	
Steel		•			•				•			•			•				•			•
Steel + Insulation			•			•			•			•			•				•			•
Steel + Insulation + Steel				•			•	•			•			•			•	•				•
Overlay + Steel + Insulation + Steel	•																					
DOOR THICKNESS	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	1-3/8" (3.5cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)	2" (5.1cm)
INSULATION	Polystyrene ¹		Polystyrene ¹	Polyurethane	Polystyrene ¹	Polystyrene ¹	Polyurethane		Polystyrene ¹	Polystyrene ¹		Polystyrene ¹	Polystyrene ¹		Polystyrene ¹	Polystyrene ¹	Polyurethane		Polystyrene ¹	Polystyrene ¹	Polystyrene ¹	
R-VALUE ²	6.48		6.64	13.35	6.64	6.48	19.40 [†] /13.35 [†]		6.64	9.05		6.64	9.05		6.64	6.48	19.40 [†] /13.35 [†]		6.64	9.05		9.05
STEEL THICKNESS																						
Gauge (ga)	27/27 ga	24 ga	24 ga	25/27 ga	25 ga	25 ga	27/27 ga	27/27 ga	25 ga	25 ga	27/27 ga	24 ga	24 ga	24/27 ga	25 ga	25 ga	27/27 ga	27/27 ga	25 ga	25 ga	27/27 ga	27/27 ga
Gauge (mm)	0.42/0.42mm	0.61mm	0.61mm	0.53/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.42/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.61mm	0.61mm	0.61/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.42/0.42mm	0.53mm	0.53mm	0.42/0.42mm	0.42/0.42mm
WOODGRAIN EXTERIOR TEXTURE	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
END STILES																						
Galvanized		•			•				•			•			•				•			•
Painted	•			•			•	•			•	•	•				•	•				•
THERMAL SEAL	•						•	•									•	†				
BOTTOM WEATHER SEAL																						
Steel Retainer		•		•	•	•		•	•		•	•	•		•	•		•	•		•	•
Aluminum Retainer	•						•							•			•					
Extruded Vinyl							•	•			•						•	†				•
DECORATIVE WINDOW OPTIONS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WINDOW GLASS OPTIONS																						
3/32" (0.24cm) Single Strength							•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1/8" (0.32cm) Tempered 2X Strength	•	•	•	•																		
Insulated Glass	•																					
Obscure	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
DECORATIVE HARDWARE OPTIONS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
EXTERIOR COLOR OPTIONS																						
True White	• ³	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Almond	• ³	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Wicker Tan	• ³	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sandtone	• ³	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Terratone		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Dark Brown		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Hunter Green								•									•					
Gray								•									•					
Black									•									•				
Golden Oak		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Walnut		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Mahogany		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WIND LOAD ⁴ AVAILABLE	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
WARRANTY																						
Paint Finish ⁵	Lifetime	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime	15 Years	25 Years	Lifetime	Lifetime
Workmanship/Hardware ⁵	5 Years	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	Lifetime	1 Year	2 Years	3 Years	3 Years	5 Years	Lifetime	1 Year	2 Years	3 Years	Lifetime	1 Year	2 Years	3 Years	3 Years



¹ Insulation on Amarr brand doors has passed self-ignition, flamespread, and smoke developed index fire testing.

² Calculated door section R-value is in accordance with DASMA TDS-163.

³ Based on independent laboratory test results.

⁴ True White Bead Board only.

⁵ All panels and colors except True White Bead Board.

[†] True White Short Panel only.

[‡] All panels and colors except True White Short Panel.

³ With White Overlay.

⁴ It is your responsibility to make sure your garage door meets local building codes.

⁵ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

NOTE: Optional door locks and various heights and widths are available thru your local garage door dealer.

WOOD SPECIFICATIONS

	AMARR® BY DESIGN AD4000
PANEL DESIGNS	
Carriage House	Unlimited Designs
CONSTRUCTION*	
Wood + Insulation + Wood	•
DOOR THICKNESS	3" (7.6cm)
WOOD BASEPLY OPTIONS	
5/8" MDO Plywood (paint grade only)	•
1/2" Marine Grade Plywood	•
5/8" Incense Cedar	•
5/8" Clear Vertical Grain Cedar	•
5/8" Red Grandis	•
5/8" Mahogany	•
Other materials available upon request	•
TRIM OVERLAY OPTIONS	
5/8" Moisture-and Rot-resistant	•
Extira Exterior Panel (paint grade only)	•
5/8" Incense Cedar	•
5/8" Clear Vertical Grain Cedar	•
5/8" Red Grandis	•
5/8" Mahogany	•
Other materials available upon request	•
OPTIONAL WOOD DISTRESSING	•
SECTION HEIGHT OPTIONS	18", 21", 28" or 32"
POLYSTYRENE INSULATION (1-3/8" thick)	•
R-VALUE	9.0
BOTTOM WEATHERSEAL	•
DECORATIVE WINDOW OPTIONS	
1/8" (0.32cm) Double Strength	•
Insulated	•
OPTIONAL DECORATIVE HARDWARE	•
WIND LOAD¹ AVAILABLE*	•
FIRE RATED DOORS AVAILABLE²	•
SECTION WARRANTY³	1 Year

¹ It is your responsibility to make sure your garage door meets local building codes.

² Optional: Special-designed doors meet guidelines for CA Building Codes for use in Wildlife Urban Interface (WUI). Fire-rated doors with insulated and tempered glass windows available.

³ For complete warranty details, visit amarr.com or contact your local Amarr dealer.

* Optional: Wood-on-steel section construction is available. Some wind load pressures may require wood-on-steel section construction.

Doors are shipped natural. Priming is available for paint grade doors. All doors require finishing on all six (6) sides of each section within two days of receipt of door(s) and prior to installation. Visit amarr.com for finishing recommendations.

HARDWARE SPECIFICATIONS

TRACK: 2" industrial grade galvanized .083 horizontal and vertical track. Standard lift 25C-15" radius or 2LC-6" low headroom clearance. For doors over 650 lbs, 3" track.

HINGES: Up to 12': Single-end 11ga graduated galvanized. 12' and over: Double-end 11ga graduated galvanized.

ROLLERS: 2" nylon 10-ball bearing commercial rollers (short stem for up to 12'; long stem for 12' and over).

STRUTS: 3" galvanized struts

COUNTER BALANCE: 10,000 cycle torsion springs, cast aluminum cable drums, 1" diameter 11ga torsion tube. For doors over 650 lbs, solid core steel shaft and coupler if exceeding 151" in length.

FASTENERS: Cadmium plated fasteners (standard) for on-door hardware and securing tracks to jambs. All hinge fasteners are factory installed with concealed bolt heads (under the trim overlay).

OPERATION: Manual push-up. No lock assembly is supplied. Electric openers with 3/4 hp recommended for best possible operation.

Doors available in various heights and widths. Hardware specifications are consistent with doors not exceeding 18' wide and 10' high. Requirements escalate with door size and weight and have limitations.

Contact your local Amarr dealer for specific details.

SPECIALTY SPECIFICATIONS

ALUMINUM	AMARR VISTA VI1000
FRAME CONSTRUCTION	2" thick aluminum
SECTION HEIGHTS	21" and 24"; 18" for odd height doors
GLASS OPTIONS	
Transparent	Clear, Obscure, ThermoPro Low-E
Opaque	Frost, Snow, Whiteout
Tint	Gray, Bronze, Green
PANEL OPTIONS	Full View, Aluminum, Insulated Aluminum, Louvered, Perforated
FINISH OPTIONS	
Anodize	Clear, Champagne, Copper, Medium Bronze, Dark Bronze, Black
Paint ⁴	26 standard PVDF colors, 21 standard Powder Coat colors, RAL and custom colors in both PVDF and Powder Coat
Mill	Perforated panel only
WIND LOAD¹ AVAILABLE	•
FINISH WARRANTY²	5 Years
WORKMANSHIP/HARDWARE WARRANTY²	5 Years

VINYL	AMARR COASTAL C03000
CONSTRUCTION	Vinyl + Insulation + ABS
DOOR THICKNESS	1-7/16"
R-VALUE	8.16
WINDOW OPTIONS	•
GLASS OPTIONS	1/8" Clear DSB (Standard), Clear Tempered, Insulated Tempered, Obscure, Insulated Obscure, Insulated
WIND LOAD¹ AVAILABLE	•
WIDTHS AVAILABLE³	8', 9', 10', 16', 18'
HEIGHTS AVAILABLE³	6' 6", 7', 7' 6", 8'
SECTION WARRANTY²	1 Year
FINISH WARRANTY²	Lifetime
HARDWARE WARRANTY²	3 Years

¹ It is your responsibility to make sure your garage door meets local building codes.

² For complete warranty details, visit amarr.com or contact your local Amarr dealer.

³ Custom widths and heights available. Upcharge applies.

⁴ For complete color availability visit amarr.com

ENTREMATIC

Entrematic

165 Carriage Court
Winston-Salem, NC 27105
800.503.DOOR
www.amarr.com



Amarr, Classica, Stratford and Oak Summit as words and logos are registered trademarks owned by Entrematic Group AB or companies within the Entrematic Group.

Technical data subject to change without notice.

Sectional door products from Entrematic may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents.

©Entrematic Group AB 2016. All rights reserved.
Form #7091216/ENT

